

UC在线式系列 UPS

1KVA-5KVA



- Pure sine wave output / 纯正弦波输出
- DSP digital control / DSP数字控制
- Boost and buck AVRfor voltage stabilization / 自动调节升压和降压，稳定电压输出
- Cold start function /冷启动功能
- Intelligent battery management /智能化电池管理
- Short circuit and overload protection / 短路和过载保护
- Off-mode charging / 关机自动充电
- Offering LED and LCD panels for selection/LED 和 LCD 面提供选择
- Optional USB/RS232/RJ45/SNMPcommunication port /可选择USB/RS232/RJ45/SNMP通讯接口




可选输出座



万用座
Universal Socket



大南非座
Type M Socket



国标座
Chinese Socket



德规座
German Socket



法式座
French Socket



美标座
US Socket



英式座
UK Socket



双联巴西座
Type N Socket

1KVA-5KVA Line Interactive UPS

APPLICATIONS/应用范围

- Personal computer / 个人电脑
 - POS(Point of sales) terminals / 税务、通信
 - Fax machine / 传真机
- Printer / 打印机
 - Security system / 安保系统
 - Modem, router / 交换机,路由器



SPECIFICATION/技术规格					
Model /型号		UC1K(S)	UC2K(S)	UC3K(S)	UC5K(S)
Capacity/容量		1000VA/800W	2000VA/1600W	3000VA /2400W	5000VA /3000W
INPUT/输入					
Voltage range/ 电压范围		145~275VAC±5V			165~275VAC±5V
Frequency range/ 频率范围		50Hz-60Hz			
OUTPUT/输出					
Output voltage /输出电压		220VAC			
AC voltage range /稳压范围		±10%			
Frequency range(Batt.Mode)/ 频率范围		50Hz±0.25Hz or 60Hz±0.3Hz			
Overload/过载		105%-110%:UPS beep alarm,do not shut down /UPS报警鸣叫			
		110%-130%:auto shut down after 30 seconds /30秒后自动关机			
		>130%;auto shut down immediately /马上自动关机			
Transfer time /转换时间		0ms			
Output waveform(Batt.Mode) /输出波形		纯正弦波 Pure sine wave			
Standard UPS/标机					
Standard UPS battery /标机电池	Battery type /电池型号	内置12V 7AH/12V 9AH/12V 17AH			
	Numbers/数量	2	4	6	4
	Maxinum charging current /最大充电电流	Assume: 1A ± 10% Max: 1A or 2A for option			
	Charging voltage /充电电压	27.3VDC±1%	54.7VDC±1%	82.0VDC±1%	54.7VDC±1%
Machine data /机器尺寸	Size L*W*H(mm)/ 尺寸	145*380*220	170*421*225	170*421*225	190*440*320
	Net weight (kgs)/净重	10.3	19	19	33
Long-run model /长延时机					
Long-run model battery /长延时机 电池	Battery type /电池型号	12V,AH depending on applicant			
	Numbers/数量	3	6	6	
	Maxinum charging current /最大充电电流	>5A			
	Charging voltage /充电电压	27.4VDC±1%	82.1VDC±1%	109.4VDC±1%	54.7VDC±1%
Machine data /机器尺寸	Size L*W*H(mm)/ 尺寸	145*380*220	170*421*225	170*421*225	190*440*320
	Net weight (kgs)/净重	6.5	11	11	-
Environment /操作环境					
Humidity/湿度与温度		20-90%RH@0-40°C(non-condensing)不结露			
Noise level/噪音		1米内少于55dB Less than 55dBA@1 Meter			
Environment 操作环境					
智能Smart RS-232		支持 Support windows 2000/2003/XP/Vista/2008, Windows7/8, Linux, Unix, and MAC			
可选SNMP /Optional SNMP		电源管理支持SNMP管理与网络管理 Power management from SNMP management and web browser			
1.Product specifications are subject to change withoutfurther notice 2.If the equipment is installed at an altitude exceeding 1000 meters, its output power will be derated by 1% for every 100 meters of elevation gain.					