

高频在线式系列单进单出三进单出

10KVA-30KVA



- Real-time Dual Conversior /真正实现在线双转换
- Microprocessor control ensures high reliability /微处理器控制确保高可靠性
- Power factor up to 0.9 /输出功率因可达0.9
- Wide input voltage range(110V-300V) /宽市点输入范围(110V-300V)
- Output sine wave,compatible with generators /输出正弦波，兼容发电机
- Optional SNMP card for independent /选配的精致SNMP卡能单独 or seamless monitoring with RS232 /或与RS232一起完美监控



10KVA-30KVA Online UPS

APPLICATIONS/应用范围

- Network Management Center /网络管理中心
 - Taxation, Communication / 税务、通信
 - Public Security, Traffic / 公安、交通
 - Industrial control / 工业控制
- Computers, banking and securities /计算机、银行证券
 - Postal service, radio and television / 邮政、广电
 - Electricity, medical care / 电力、医疗
 - National defense / 国防



10KVA-30KVA Online UPS

SPECIFICATION/技术规格					
MODEL/型号		3C10K(S)	3C15K(S)	3C20K(S)	3C30K(S)
Capacity/容量		10KVA / 8000W	15KVA / 12000W	20KVA / 16000W	30KVA / 24000W
Input/Output Mode/输入输出模式		Three-input single-output			
INPUT/输入					
Voltage/电压		380/400/415VAC(3ph+N)			
Voltage range/电压范围		190-520VAC(3-phase+N)@50% load 负载； 305-520VAC(3-phase)@100% load 负载			
Frequency/频率		46-54Hz or 56-64Hz			
Power Factor/功率因数		≥0.8@100% load			
Number of Parallel Units/并机数量		-			
OUTPUT/输出					
Voltage/电压		208/220/230/240VAC			
Output Power Factor/输出功率因数		-			
Voltage(battery mode)/电压（电池模式）		± 1 %			
Frequency Tracking Range/频率跟踪范围		46-54Hz / 56-64Hz			
Frequency(battery mode)/频率（电池模式）		50Hz/60Hz±0.2Hz			
Peak Factor/峰值系数		3:1 （Peak Value） / （最大值）			
Harmonic Distortion/谐波失真		≤3% THD (Linear Load)/(线性负载) ； ≤ 5% THD (Non-linear Load)/(非线性负载)			
Transfer Time	AC Mode to Batt. Mode/交流至直流	0ms			
转换时间	Inverter to Bypass/逆变至旁路	<4ms			
EFFICIENCY/效率					
AC Mode/市电模式		91%	91%	93%	91%
Battery Mode/电池模式		91%	91%	92%	90%
BATTERY/电池					
	Battery model / 电池的型号	取决于申请商 Depends on the applicant			
Standard Model 标准机型	standard charging time/标准充电时间	-			
	Maximum charging current/最大充电电流	-			
Long-run Model 长机	Battery Numbers/电池数量	16-20 adjustable (可调整)			
	Maximum charging current/最大充电电流	可预设Preset 4A,可调整1A/2A/4A adjustable			
	Charging voltage/充电电压	218.4VDC±1%, 273VDC±1%			
INDICATORS/显示					
LCD		Load level,Battery level, AC mode ,Battery mode,input voltage,Output voltage,Bypass mode,Fault prompt 负载大小, 电池容量,市电模式, 电池模式,输入电压,输出电压, 旁路模式, 故障指示			
ENVIRONMENT/环境					
Operation Humidity/湿度		20-95%RH@0-45℃（No condensation 不结露）			
Noise Level/噪音		< 60dbA@1M			
MANAGEMENT/管理					
智能 Smart RS-232/USB		持 Supports Windows@2000/2003/XP/Vista/2008, Windows@7/8, Linux, and MAC			
可选 Optional SNMP		电源管理支持SNMP管理与网络管理Power management supports SNMP management and network management			
PHYSICAL/物理					
Standard Model	N.W.(kg)净重 (kg)	-	-	-	-
标准机型	Dimension D*W*H(mm) 尺寸	-	-	-	-
Long-run Model	N.W.(kg)净重 (kg)	27	35	35	64
长延机型	Dimension D*W*H(mm) 尺寸	575*248*620			815*250*826
1.Product specifications are subject to change without further notice 2.If the equipment is installed at an altitude exceeding 1000 meters, its output power will be derated by 1% for every 100 meters of elevation gain.					